

## SKS 225

## SS Ball Valve

### SS 304 (CF 8) Screwed

"SKS" SS 304 (CF 8) Single / Two piece design, full bore lever operated ball valve, blow out proof stem floating ball, ANSI #800, BSPT screwed female end.



Sr. No.	Part Name	Details
1	Body	S.S. 304 (CF8)
2	Cap	S.S. 304 (CF8)
3	Ball	S.S. 304 (CF8)
4	Seat	Pure P.T.F.E.
5	Stem	S.S. 304 (CF8)
6	Handle	S.S. 304 (CF8)
7	Packing	Pure P.T.F.E.
8	Seal Gasket	Pure P.T.F.E.
9	Nut	S.S. 304 (CF8)
10	Lever Sleeve	PVC
11	Pressure Rating	1000PSI
12	Temperature Rating	-20°C to 180°C

**Dimensions/Technical details on Request**  
Size : 1/4" (6mm) to 2" (50mm)

## SKS 236

## SS 3 Piece Design Ball Valve

### SS 316 (CF 8M) Screwed

"SKS" SS 316 (CF 8M) three piece design, full bore lever operated ball valve, blow out proof stem, floating ball, ANSI #800, BSPT screwed end.



**Dimensions/Technical details on Request**  
Size : 1/2" (15mm) to 3" (80mm)

Sr. No.	Part Name	Details
1	Body	S.S. 316 (CF8M)
2	Cap	S.S. 316 (CF8M)
3	Ball	S.S. 316 (CF8M)
4	Seat	Pure P.T.F.E.
5	Stem	S.S. 316 (CF8M)
6	Handle	S.S. 316 (CF8M)
7	Packing	Pure P.T.F.E.
8	Seal Gasket	Pure P.T.F.E.
9	Nut	S.S. 316 (CF8M)
10	Lever Sleeve	PVC
11	Pressure Rating	1000PSI
12	Temperature Rating	-20°C to 180°C

## SKS 230

## CI Ball Valve



**DESCRIPTION** : CI Ball Valve, 3 Pc Design, Flanged Ends, to ASA#150

**MOC BODY** : CI (SKS 230)

**INTERNALS** : SS304

**SIZE** : 1" TO 16"

## SKS 210

## SS 3 Piece Design Ball Valve

### CS (WCB) Screwed / Socket - Weld

"SKS" C.S. (ASTM A 216 Gr. WCB) three piece design, full bore lever operated ball valve, blow out proof stem, floating ball, ANSI #800, (BSPT Screwed/Socket weld) End.

- Manufactured to BS 5351
- Tested to BS 6755 (Part 1).
- Screwed female ends to BSP / BSPT / NPT
- Socket weld ends to ANSI B 16.11.



**Dimensions/Technical details on Request**  
Size : 1/2" (15mm) to 2" (50mm)

Sr. No.	Part Name	Details
1	Body	ASTMA 216 Gr. WCB
2	Body Connector	ASTMA 216 Gr. WCB
3	Ball	S.S. 304(CF8)
4	Seat	Pure P.T.F.E.
5	Stem	S.S. 304 (CF8)
6	Body Seal	Pure P.T.F.E.
7	Gland Packing	Pure P.T.F.E.
8	Stem Seal	Pure P.T.F.E.
9	Studs	S.S. 304 (CF8)
10	Nuts	S.S. 304 (CF8)
11	Lever Sleeve	PVC
11	Pressure Rating	1000PSI
12	Temperature Rating	-20°C to 180°C

## SKS 220, 240, 246

## CS/SS Ball Valve

### Flanged end

C.S. (WCB) / S.S. 304 (CF 8) / S.S. 316 (CF 8M) three piece design, full bore ball valve, blow out proof stem, floating ball, ANSI # 150 & 300, flanged end.

#### Main Features :

- Manufacturing standard: BS 5351
- Testing standard : BS 5146 /6755
- Face to Face : ANSI B 16.10
- End Connections : Flanged end to ANSI B 16.5 RF / BS 10 / IS 6392. Special flanged connection available on request. Valves up to 50mm with hand levers, 65mm & above with extension handles.



Sr. No.	Part Name	Details
1	Body	ASTMA 216 Gr. WCB / ASTM A351 Gr. CF8 /CF 8M
2	Body Connector	ASTMA 216 Gr. WCB / ASTM A351 Gr. CF8 /CF 8M
3	Connector Seal	Pure P.T.F.E.
4	Ball Seat	Pure P.T.F.E.
5	Ball	ASTMA Gr. 351 CF8 /CF 8M
6	Stem	ASTMA Gr. 351 CF8 /CF 8M
7	Stem Seal & Gland Packing	Pure P.T.F.E.
8	Gland	S.S. /M.S.
9	Lever	S.S. /M.S.
10	Lever Nuts	S.S. /M.S.
11	Body Studs	S.S. /M.S.
12	Body Nuts	S.S. /M.S.
13	Lever Sleeve	PVC

**Dimensions/Technical details on Request**  
Size : 1/2" (15mm) to 8" (200mm) / for sizes above 8" (200mm) - (on Request)